

## Sealed Gel Rechargeable Battery Product Specification

### SLAUMXNPG12-12 (12V12AH)




#### Specifications

Nominal Voltage		12V
Rated capacity (20 hour rate)		12Ah
Dimensions	Total Height	98 mm (3.86 inches)
	Height	93 mm (3.66 inches)
	Length	151 mm (5.94 inches)
	Width	98 mm (3.86 inches)
Weight Approx		4.03 Kg (8.87 lbs)


#### Characteristics

Capacity 25°C(77°F)	20 hour rate(0.60 A)	12.0 AH
	10 hour rate(0.30 A)	11.4 AH
	5 hour rate(2.04A)	10.2 AH
	1 hour rate(6.60A)	6.40 AH
	1.5 hour discharge to 10.5V	4.80 A
Internal Resistance	Full charged Battery at 25°C(77°F)	13 mΩ
Capacity affected by Temperature (20 hour rate)	40°C(104°F)	102%
	25°C(77°F)	100%
	0°C(32°F)	85%
	-15°C(5°F)	70%
Self-Discharge at 25°C(77°F)	Capacity after 1 month storage	92%
	Capacity after 3 month storage	90%
	Capacity after 6 month storage	80%
Terminal		T2
Charge (constant Voltage)	Cycle	Maximum Charging Current 3.60 A Voltage 13.80-14.40V
	Float	Voltage 13.50-13.80V


#### Outer dimensions (mm)



#### Terminal Type (mm)



#### Discharge Curves 25 °C(77 °F)



Constant Current(Amp) and Constant Power(Watt) Discharge Table at 25 °C(77 °F)

Time		5 Min	10 Min	15 Min	30 Min	1hr	2Hr	3Hr	4Hr	5Hr	10Hr	20Hr
9.60V	A	50.3	30.4	22.9	13	8.21	4.42	3.18	2.56	2.2	1.26	0.65
	W	508.8	340.8	265.2	148.8	91.8	53.16	37.68	31.08	26.58	15.24	7.92
10.20V	A	45.1	28.5	21.7	12.5	7.97	4.25	3.05	2.46	2.11	1.21	0.636
	W	468	320.4	247.8	139.8	89.4	51.42	36.3	29.82	25.62	14.7	7.62
10.50V	A	42.1	26.6	20.8	12.1	7.76	4.1	2.94	2.39	2.06	1.18	0.621
	W	445.8	302.4	229.2	130.8	87.6	49.92	35.1	28.92	24.9	14.28	7.32
10.80V	A	38.4	24.3	19.6	11.7	7.53	3.92	2.78	2.27	2	1.14	0.598
	W	416.4	278.4	205.2	118.2	84.6	48.18	33.6	27.72	24.18	13.92	7.08
11.10V	A	32.6	20.9	18.2	10.9	7.02	3.63	2.57	2.09	1.92	1.09	0.574
	W	367.2	242.4	166.8	100.8	78.6	45.48	31.5	26.22	23.28	13.38	6.78